

2010 BMW G 450 X

MSRP: \$8,200.00* Destination charge (not included in MSRP): \$495



Copyright 2010 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Liquid-cooled, single-cylinder 4-stroke	Front Wheel	1.60 x 21 wire spoke
Bore x Stroke	98 mm x 60 mm	Rear Wheel	2.15 x 18 wire spoke
Displacement	450 cc	Front Tire	90/90 x 21
Horsepower	41 bhp @ 7000 rpm	Rear Tire	140/80 x 18
Torque	32 lb/ft @ 6500 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	86.6 inches
Valve Gear	DOHC chain driven	Overall Width	31.7 inches
Valves	2 x 40 mm intake / 2 x 33 mm exhaust	Wheelbase	58.0 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	1.1 quarts	Seat Height	37.6 inches
Engine Management	Digital Motor Electronic (DME)	Steering Angle	61.8 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.7 inches
Fuel Tank	Plastic cell w/enclosed pump & filter	Weight - Dry	245 lbs. excluding accessories
Fuel Capacity	1.8 U.S. gallons	Weight - Wet	267 lbs. excluding accessories
Charging System	180 Watts @ 14 Volts	Maximum Load	617 lbs. GVWR
Battery	12 Volts 7 Amps/hour	Standard Colors	
Cooling System	Single Radiator, 50/50 water/anti-freeze mix	Code Price	Description
Drivetrain		N57 N / C	Racing White 10
Primary Drive	1:2.618	Standard Equipment	
Clutch	Multiple plate in oil bath	146 N / C	US 50 State Street Legal
1st Gear Ratio	2.46:1	Available Equipment	
2nd Gear Ratio	1.71:1	133 \$250	Racing Silencer (additional, slip-on)
3rd Gear Ratio	1.35:1		
4th Gear Ratio	1.04:1		
5th Gear Ratio	0.88:1		
6th Gear Ratio	N/A		
Final Drive System	Chain		
Final Drive Ratio	15 / 48 tooth sprockets		
Frame and Suspension			
Frame	Stainless Steel Precision Tube		
Front Suspension	Marzocchi UPSD fork 45 mm		
Front Travel	11.8 inches		
Rear Suspension	Direct Mounted Ohlins Shock		
Rear Travel	12.6 inches		
Brakes			
Brake System	Brembo single front and rear disc		
Front Brakes	Brembo 2 piston floating caliper		
Front Rotor	10.2 inch single rotor		
Rear Brake	Brembo single piston floating caliper		
Rear Rotor	8.7 inch single rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		