

2010 BMW R 1200 GS

MSRP: \$14,950.00* Destination charge (not included in MSRP): \$495



Copyright 2010 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	2.50 x 19 cast aluminum
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	4.0 x 17 cast aluminum
Displacement	1170 cc	Front Tire	110/80 x 19 tubeless
Horsepower	110 bhp @ 7750 rpm	Rear Tire	150/70 x 17 tubeless
Torque	88 lb/ft @ 6000 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	87.0 inches
Valve Gear	DOHC, chain driven, radial layout w/ cam followers	Overall Width	36.6 inches
Valves	2 x 39 mm intake / 2 x 33 mm exhaust	Wheelbase	59.3 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	4.2 quarts	Seat Height	33.5 inches
Engine Management	BMW Engine Controller - BMS K+	Steering Angle	64.3 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.0 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	448 lbs. excluding options & accessories
Fuel Capacity	5.3 U.S. gallons including 1 gallon reserve	Weight - Wet	504 lbs. excluding options & accessories
Charging System	720 Watts @ 14 Volts	Maximum Load	968 lbs. GVWR
Battery	12 Volts 14 Amps/hour maintenance-free	Available Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		751 N / C	Alpine White
Primary Drive	1:1.737	N15 N / C	Magma Red
Clutch	180 mm dry, single plate with hydraulic actuation	N43 N / C	Sapphire Black Metallic
1st Gear Ratio	2.38:1	N50 N / C	Ostra Grey Metallic Matt
2nd Gear Ratio	1.70:1	Available Equipment	
3rd Gear Ratio	1.30:1	350 \$150	Chrome Exhaust
4th Gear Ratio	1.07:1	416 \$800	Enduro ESA
5th Gear Ratio	0.94:1	499 \$250	Low Suspension (31.1 inch; incl. 776 / not w/ 416)
6th Gear Ratio	0.85:1	519 \$250	Heated Hand Grips
Final Drive System	Enclosed driveshaft with two universal joints	530 \$250	Tire Pressure Monitor (TPM)
Final Drive Ratio	2.91:1	539 \$295	On Board Computer (Incl. Oil Level Warning)
Frame and Suspension		589 \$100	Hand Protection
Frame	Tubular steel trellis frame	603 \$395	Anti-Theft Alarm
Front Suspension	BMW Telelever	630 \$1100	Integral ABS (Disconnectable)
Front Travel	7.5 inches	650 \$400	Enduro ASC (only with 630)
Rear Suspension	BMW EVO Paralever	681 \$200	Saddle Bag Mounts
Rear Travel	7.9 inches	771 \$500	Cross Spoke Wheels
Brakes		776 N / C	Low Seat (32.3 inches)
Brake System	BMW		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.0 inch Dual Rotors		
Rear Brake	Single, two-piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		